



BUILDING CODE COMPLIANCE OFFICE (BCCO)
PRODUCT CONTROL DIVISION

MIAMI-DADE COUNTY, FLORIDA
METRO-DADE FLAGLER BUILDING
140 WEST FLAGLER STREET, SUITE 1603
MIAMI, FLORIDA 33130-1563
(305) 375-2901 FAX (305) 375-2908

NOTICE OF ACCEPTANCE (NOA)

Gaco Western LLC
P.O. Box 88698
Seattle, WA 98138

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed by Miami-Dade County Product Control Division and accepted by the Board of Rules and Appeals (BORA) to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Division (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. BORA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Division that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code and the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: GACO WESTERN ROOF COATING SYSTEMS

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA revises NOA No. 07-0509.08 and consists of pages 1 through 4.
The submitted documentation was reviewed by Jorge L. Acebo.

NOA No.: 08-0613.04
Expiration Date: 05/31/12
Approval Date:
Page 1 of 4

ROOFING COMPONENT APPROVAL

Category: Roofing
Sub-Category: Coatings
Material: Acrylic/Silicone

SCOPE:

This approves "GACO WESTERN ROOF COATING SYSTEMS" as a roof maintenance coatings manufactured by Gaco Western LLC, as described in this Notice of Acceptance, designed to comply with the Florida Building Code and the High Velocity Hurricanes Zone.

EVIDENCE SUBMITTED:

| <u>Test Agency</u> | <u>Test Identifier</u> | <u>Test Name/Report</u> | <u>Date</u> |
|---|------------------------|-----------------------------------|-------------|
| PRI Construction Materials Technologies | GWI-002-02-201 | ASTM D 6083 Fed Spec TT-C-555B | 01/09/07 |
| | GWI-001-02-01 | ASTM D 6694 Fed Spec TT-C-555B | 04/10/07 |
| | GWI-004-02-01 | ASTM D 6694 Fed Spec TT-C-555B | 05/13/08 |
| Underwriters Laboratories | Project 04NK27341 | UL 790 | 02/01/05 |
| | Project 07NK02171 | UL 790 | 03/13/07 |
| | Project 08NB01503 | UL 790 | 02/21/08 |
| Factory Mutual Research Corp. | 3023644 | 4470 | 02/02/07 |

PHYSICAL PROPERTIES OF COMPONENTS

Trade names: **A3100R Acrylic Top Coat**

Thickness: For application over spray polyurethane foam system apply a base coat at a minimum rate of 1.13 gal/100 ft², an intermediate coat at a minimum rate of 1.13 gal/100 ft², and a top coat at a minimum rate of 1.13 gal/100 ft².
For application of a recover coating over an existing acrylic roof apply a base coat at a minimum rate of 1 gal/100 ft², and a top coat at a minimum rate of 1 gal/100 ft².

Specifications: ASTM D 6083

Description: An acrylic white elastomeric quick set coating membrane applied to; spray polyurethane foam roof systems and a recover of any existing acrylic roof.

Container Size: 5, 55 gallons. Note all precautions on container.

Systems Approvals: Methods of application and quantities shall comply with specific Roof Assembly, Product Control Notice of Acceptance.

Trade names: **S 1000 Top Coat**

Thickness: For application over spray polyurethane foam system apply a base coat at a minimum rate of 1.1 gal/100 ft and a top coat at a minimum rate of 1.1 gal/100 ft².

For application of a recover coating over an existing silicone roof apply a base coat at a minimum rate of 1.1 gal/100 ft², and a top coat at a minimum rate of 1.1 gal/100 ft².

Specifications: ASTM D 6694

Description: A single component, air dried, silicone-based rubber elastomeric membrane coating that is brush, roller or spray-applied. To be applied to spray polyurethane foam roof systems and as a recover of any existing silicone roof coatings.

Container Size: 5 and 55 gallons. Note all precautions on container.

Systems Approvals: Methods of application and quantities shall comply with specific Roof Assembly, Product Control Notice of Acceptance.

Trade names: **S-2000 Solventless Silicone Basecoat/Top Coat**

Thickness: For all applications apply 2 coats; a base coat at a minimum rate of .75 gal/100 ft and a top coat at a minimum rate of .75 gal/100 ft².

- Spray Polyurethane Foam Roof Systems
- Acrylic Coatings
- Galvanized Metal Roofs (in conjunction with E5320 2 part Epoxy Primer)
- Smooth Built Up Roof Systems (in conjunction with E5320 2 part Epoxy Primer)
- EPDM Single Ply Roof Systems (in conjunction with E5320 2 part Epoxy Primer)
- PVC Single Ply Roof Systems (in conjunction with E5320 2 part Epoxy Primer)

Specifications: ASTM D 6694

Description: A single component, moisture cured, silicone-based rubber elastomeric membrane coating that is brush, roller or spray-applied to the roof covers listed above.

Container Size: 5 and 55 gallons. Note all precautions on container.

Systems Approvals: Methods of application and quantities shall comply with specific Roof Assembly, Product Control Notice of Acceptance.